- (3) The center frequency of each channel requested, the maximum effective radiated power, the effective radiated power in each of the cardinal radial directions, any non-standard emission types to be used, including bandwidth and modulation type, the transmitter classification (e.g. central office), and the locations and call signs, if any, of any fixed points of communication.
- (c) No landline facilities. Each application for a central office station must contain an exhibit showing that it is impracticable to provide the required communication service by means of landline facilities.
- (d) Interference exhibit. Applications for central office, interoffice and relay stations must include an exhibit identifying co-channel facilities and demonstrating, in accordance with §22.715 that the proposed station, if authorized, would not cause interference to the service of those co-channel facilities. This exhibit must:
- (1) For UHF channels, identify each protected transmitter located within 108 kilometers (67 miles) of the proposed transmitter in directions in which the distance to the interfering contour is 76.4 kilometers (47.5 miles) or less, and within 178 kilometers (111 miles) of the proposed transmitter in directions in which the distance to the interfering contour exceeds 76.4 kilometers (47.5 miles); and identify each protected Basic Exchange Telephone Radio System central office transmitter in the rural Radiotelephone Service within 231 kilometers (144 miles).
- (2) For VHF channels, identify each protected transmitter located within 135 kilometers (84 miles) of the proposed transmitter in directions in which the distance to the interfering contour is 93.3 kilometers (58 miles) or less, and within 178 kilometers (111 miles) of the proposed transmitter in directions in which the distance to the interfering contour exceeds 93.3 kilometers (58 miles).
- (3) For each protected transmitter identified, show the results of distance calculations indicating that there would be no overlap of service and interfering contours, or alternatively, indicate that the licensee of or applicant for the protected transmitter and/

or the applicant, as required, have agreed in writing to accept any interference resulting from operation of the proposed transmitter.

(e) Blocking probability. Applications for authority to operate basic exchange telephone radio systems (BETRS) that request more than two channel pairs must include an exhibit containing calculations showing that the number of channels requested is the minimum necessary to achieve the required grade of service (in terms of blocking probability), and that there will be adequate spectrum available in the area to meet realistic estimates of current and future demand for paging, two-way mobile and rural radiotelephone services (see §22.719(c)). Applications for authority to operate new conventional rural radiotelephone systems that request more than two channel pairs must include a statement explaining why BETRS technology is not being proposed.

[59 FR 59507, Nov. 17, 1994, as amended at 59 FR 59954, Nov. 21, 1994]

§ 22.711 Provision of information to applicants.

Licensees in the Rural Radio Service must, upon request by a bona-fide prospective applicant, provide to such applicant the information required by §22.709 regarding the portion of the licensee's operations that potentially could affect, or be affected by, the prospective applicant's proposed station, if such information is not already on file with the FCC. This information must be provided to the bona-fide prospective applicant no later than 30 days after receipt of the information request.

[59 FR 59954, Nov. 21, 1994]

§22.713 Construction period for rural radiotelephone stations.

The construction period for stations in the Rural Radiotelephone Service is 12 months.

§22.715 Technical channel assignment criteria for rural radiotelephone

Channels are assigned in the Rural Radiotelephone Service using the procedures in §22.567.